

ROLLSROLLER

FLATBED APPLICATOR

PRECISION. SPEED. CONTROL.



SLIM

ROLLSROLLER

THE SMART ENTRY INTO PROFESSIONAL APPLICATION

Move from manual work to faster, more consistent production.

ROLLSROLLER SLIM is designed to make professional flatbed application accessible to more businesses worldwide. It is built on the proven ROLLSROLLER application method, delivering controlled, precise and reliable results – in a simplified and cost-efficient format. SLIM is the ideal starting point for businesses looking to move away from manual application and into a more efficient, professional workflow.



Developed and manufactured by ROLLSROLLER AB in Sweden
rollsroller.com

SLIM is the fastest way to move from manual application to professional production.

TECHNICAL SPECIFICATIONS

MODEL NAME	ROLLSROLLER 160 / 100 Slim	ROLLSROLLER 160 / 147 Slim
Part No.	122-040	122-041
Flatbed Length/Width	1640 mm / 1000 mm 5 ft. 4.6 in. / 3 ft. 3.4 in.	1640 mm / 1470 mm 5 ft. 4.6 in. / 4 ft. 9.9 in.
Working area Length/Width	1240 mm / 930 mm 4 ft. 0,8 in. / 3 ft. 0,6 in.	1240 mm / 1400 mm 4 ft. 0,8 in. / 4 ft. 7,1 in.
Work height Flatbed	850 mm / 2 ft. 9,5 in.	850 mm / 2 ft. 9,5 in.
Overall width incl. mounted Glide Beam	1270 mm / 4 ft. 2 in.	1740 mm / 5 ft. 8,5 in.
Overall height incl. mounted Glide Beam	1150 mm / 3 ft. 9,3 in.	1150 mm / 3 ft. 9,3 in.
Weight Flatbed Applicator	155 kg / 342 lb	185 kg / 408 lb
Flatbed surface	Tempered glass + Cutting Mat	
Required air supply	6-8 bar / 0,6-0,8 MPa	6-8 bar / 0,6-0,8 MPa
Set pressure during operation	3-6 bar / 0,3-0,6 MPa	3-6 bar / 0,3-0,6 MPa
Total packing weight (Flatbed Applicator + package)	210 kg / 463 lb	250 kg / 551 lb
Package Flatbed Applicator Assembled (LxWxH)	1750 x 460 x 1750 mm / 5 ft. 8,9 in. x 1 ft. 6,1 in. x 5 ft. 8,9 in.	1750 x 460 x 1750 mm / 5 ft. 8,9 in. x 1 ft. 6,1 in. x 5 ft. 8,9 in.
Wheels	No	
Warranty	3 year limited warranty *	
User Manual	ENG	

* Visit rollsroller.com/our-products/warranty/ for more information

ACCESSORIES LIST

ARTICLE NUMBER	ITEM NAME	MODEL	COMMENT
126-126	Roll holder short side, Slim 100	160/100 Slim	Support and position the media roll at the end of the table. Improves material handling, saves time and creates a smoother workflow
126-127	Roll holder short side, Slim 147	160/147 Slim	
111-049	LED Slim 160/100	160/100 Slim	Improves visibility across the entire work surface during application.
111-050	LED Slim 160/147	160/147 Slim	Enables more precise alignment and reduces application errors.
10059	Core holder 40mm / 1,57 in. (2pcs)	All models	Ensure stable rotation of the media roll during application.
126-137	Bed end tray Slim 100	160/100 Slim	Provides practical storage space at the end of the table for tools and materials. Keeps essential items within easy reach and supports a more organized workflow. Comes in navy blue and sold individually.
126-138	Bed end tray Slim 147	160/147 Slim	
126-125	Air Blow Gun Slim	All models	Removes dust and particles from the surface before application
126-140	KeenCut Evo 3 Smartfold 160	160/147 Slim	Not available for model 100. Enables efficient cutting and application in the workflow.
10099	Stop Static kit 1m wire/1pc magnet	All models	Reduces static electricity during application
126-136	Dual-side control & emergency stop	All models	Enables operation from both sides of the table for greater flexibility during daily use. Improves workflow and enhances operator safety by providing quick access to the emergency stop from either side.
79200	Vinyl remover	160/147 Slim	Helps remove excess vinyl material quickly and efficiently during production. Reduces manual efforts and supports a faster, cleaner workflow.
126-145	Mobility kit, SLIM (castors)	All models	Makes it simple to reposition the machine within the workspace.

HEADQUARTERS

ROLLSROLLER® AB Gräsdalsgatan 6
SE 653 43 Karlstad, SWEDEN
Phone: +46 54 770 70 10
E-mail: info@rollsroller.com

USA SALES OFFICE

ROLLSROLLER INC. USA
150 North Michigan Avenue
Suite 1950, Chicago IL 60601
E-mail: info@rollsroller.com

rollsroller.com
#ROLLSROLLER

ROLLSROLLER

FLATBED APPLICATOR

PRECISION. SPEED. CONTROL.



SLIM

ROLLSROLLER

THE SMART ENTRY INTO PROFESSIONAL APPLICATION

Move from manual work to faster, more consistent production.

ROLLSROLLER SLIM is designed to make professional flatbed application accessible to more businesses worldwide. It is built on the proven ROLLSROLLER application method, delivering controlled, precise and reliable results – in a simplified and cost-efficient format. SLIM is the ideal starting point for businesses looking to move away from manual application and into a more efficient, professional workflow.



Developed and manufactured by ROLLSROLLER AB in Sweden
rollsroller.com

SLIM is the fastest way to move from manual application to professional production.

TECHNICAL SPECIFICATIONS

MODEL NAME	ROLLSROLLER 300 / 170 Slim	ROLLSROLLER 360 / 170 Slim
Part No.	122-042	122-043
Flatbed Length/Width	3040 mm / 1700 mm 9 ft. 11.7 in. / 5 ft. 6.9 in.	3640 mm / 1700 mm 11 ft. 11.3 in. / 5 ft. 6.9 in.
Working area (Roller width) Length/Width	2640 mm / 1630 mm 8 ft. 7.9 in. / 5 ft. 4.2 in.	3240 mm / 1630 mm 10 ft. 7.6 in. / 5 ft. 4.2 in.
Work height Flatbed	850 mm / 2 ft. 9,5 in.	850 mm / 2 ft. 9,5 in.
Overall width incl. mounted Glide Beam	1970 mm / 6 ft. 5,6 in.	1970 mm / 6 ft. 5,6 in.
Overall height incl. mounted Glide Beam	1150 mm / 3 ft. 9,3 in.	1150 mm / 3 ft. 9,3 in.
Weight Flatbed Applicator	295 kg / 650 lb	335 kg / 739 lb
Flatbed surface	Tempered glass + Cutting Mat	
Required air supply	6-8 bar / 0,6-0,8 MPa	6-8 bar / 0,6-0,8 MPa
Set pressure during operation	3-6 bar / 0,3-0,6 MPa	3-6 bar / 0,3-0,6 MPa
Total packing weight (Flatbed Applicator + package)	410 kg / 904 lb	455 kg / 1003 lb
Package Flatbed Applicator Assembled (LxWxH)	3100 x 460 x 1970 mm / 10 ft. 2 in. x 1 ft. 6,1 in. x 6 ft. 5,6 in.	3700 x 460 x 1970 mm / 12 ft. 1,7 in. x 1 ft. 6,1 in. x 6 ft. 5,6 in.
Wheels	No	
Warranty	3 year limited warranty *	
User Manual	ENG	

* Visit rollsroller.com/our-products/warranty/ for more information

ACCESSORIES LIST

ARTICLE NUMBER	ITEM NAME	MODEL	COMMENT
111-051	LED Slim 300/170	300/170 Slim	Improves visibility across the entire work surface during application.
111-052	LED Slim 360/170	360/170 Slim	Enables more precise alignment and reduces application errors.
10059	Core holder 40mm / 1,56in (2pcs)	All models	Ensure stable rotation of the media roll during application
126-125	Air Blow Gun, Slim	All models	Removes dust and particles from surface before application
10099	Stop Static kit 1m wire/1pc magnet	All models	Reduces static electricity during application
126-136	Dual-side control & emergency stop	All models	Enables operation from both sides of the table for greater flexibility during daily use. Improves workflow and enhances operator safety by providing quick access to the emergency stop from either side.
71854	Vinyl remover	300/170, 360/170	Helps remove excess vinyl material quickly and efficiently during production. Reduces manual efforts and supports a faster, cleaner workflow.
126-128	Roll holder short side	300/170, 360/170	Support and position the media roll at the end of the table. Improves material handling, saves time and creates a smoother workflow
129-139	Bed end tray Slim 170	300/170, 360/170	Provides practical storage space at the end of the table for tools and materials. Keeps essential items within easy reach and supports a more organized workflow. Comes in navy blue and sold individually.
71868	KeenCut Evo3 Smartfold	300/170, 360/170	Enables efficient cutting and application in the workflow.
126-145	Mobility kit, SLIM (castors)	All models	Makes it simple to reposition the machine within the workspace.

HEADQUARTERS

ROLLSROLLER® AB Gräsdalsgatan 6
SE 653 43 Karlstad, SWEDEN
Phone: +46 54 770 70 10
E-mail: info@rollsroller.com

USA SALES OFFICE

ROLLSROLLER INC. USA
150 North Michigan Avenue
Suite 1950, Chicago IL 60601
E-mail: info@rollsroller.com

rollsroller.com
#ROLLSROLLER